



SUU250 SERIES

250W U-bracket Switching Power Supplies For I.T.E.

Features:

- Wide Input Voltage 100 to 240 VAC, 47 to 63 Hz
- Internal EMI filter
- Single Output
- Input connector mates with DINKLE#DT-2G-B01W-02P and DINKLE#ESK750V-02P.
- Output connector mates with DINKLE#DT-2G-B01W-(04P or 06P) and DINKLE#ESK750V-(04P or 06P).
- Output Voltage Available 12,24,48 VDC
- Input Surge Current and Over Load protection
- Over Voltage Protection (Crowbar Design)
- Active Power Factor Correction
- Class I
- Zero Voltage Switching(ZVS) & High Efficiency up to 93%.
- 2 year warranty

Description:

The SUU250 series of compact, open frame constructed, AC/DC switching mode power supplies provide 250 Watts of continuous output power. They are suited for use in disc drive systems, microprocess or based systems, portable equipments and many other applications. All models meet FCC Part-15 class B and CISPR-22 class B emission Limits and are designed to comply with UL/c-UL(UL60950-1:2nd Edition), TUV/Bauart(EN60950-1:2nd Edition) and new CE, FCC requirements. All units are 100% burned in and tested.

Safety Approvals :



Electrical Characteristics:

Sym.	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V _{in}	Input Voltage	Operating Voltage	100		240	VAC
f _{in}	Input Frequency		47		63	Hz
PF	Power Factor Correction	I _o =Full load, V _{in} =100~240VAC	0.95	0.97	1.0	
P _o	Output Power Range	V _{in} =100 to 240 VAC	0		250	W
V _o	Output Voltage Range		See rating Chart			V
I _o	Output Current Range		See rating Chart			A
I _{il}	Input Current (Low Line)	I _o =Full load, V _{in} =115VAC			3.3	A
I _{ih}	Input Current (High Line)	I _o =Full load, V _{in} =230VAC			1.23	A
I _{rl}	Low Line Inrush Current	I _o =Full load, 25°C, Cool start, V _{in} =115VAC		12	15	A
I _{rh}	High Line Inrush Current	I _o =Full load, 25°C, Cool start, V _{in} =230VAC		25	30	A
Eff	Efficiency	I _o =Full load, V _{in} =230VAC	89	91	93	%
REG-i	Line Regulation	I _o =Full load		0.5	1	%
REG-o	Load Regulation	V _{in} =230VAC		3	5	%
OVP	Over Voltage Protection		112		132	%
OCP	Over Current Protection		110		150	%
T _{tr}	Time of Transient Response	I _o =Full load to Half Load, V _{in} =100VAC			4	mS
T _{hold}	Hold-Up Time	I _o =Full load, V _{in} =110VAC	12			mS
T _s	Start Up Time	I _o =Full load, V _{in} =100VAC	0.3	1	2	S
V _{p-p}	Ripple & Noise (Peak to Peak)	Full load, V _{in} =90VAC		0.5	1	%
I _{lk}	Safety Ground Leakage Current	I _o =Full load, V _{in} =240VAC		0.5	0.75	mA
TC	Temperature Coefficient	All output	-0.04		0.04	%/°C

Environmental :

Sym.	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
T _{oper}	Operating Temperature		0	50	70	°C
T _{stg}	Storage Temperature		-40		85	°C
H _r	Relative Humidity		5		95	%
MTBF	Operating Temperature at 25°C, Calculated per MIL-HDBK-217F		0.1M			Hrs
P _d	Derate linearly from 100% load at 50°C to 50% load at 70°C					

