

SPU15A 15WATT SERIES

Features:

- * Universal AC Input 90-264Vac, 47-63Hz
- * IEC 320-C14 Input Inlet
- * No minimum load requirement
- * 100% burn in test
- * 2 year warranty
- * Class 1 Insulation
- * Safety: UL, cUL, TUV/GS, CB, CE



SPECIFICATION:

MODEL NO.	SPU15A-1-3.3	SPU15A-1-5	SPU15A-1-6	SPU15A-1-7	SPU15A-2-9	SPU15A-3-12	SPU-15A-4-15	SPU15A-5-18	SPU-15A-6-24
PART NO.	S2113ST	S2095ST	S2096ST	S2097ST	S2235ST	S2099ST	S2100ST	S2101ST	S2102ST
OUTPUT:									
Voltage	3.3V	5V	6V	7.5V	9V	12V	15V	18V	24V
Current (Max)	2.5A	2.4A	2.0A	1.6A	1.6	1.25A	1.0A	0.83A	0.62A
Current (Min)	0A								
Line Regulation	+/-1% Max								
Load Regulation	+/-7% Max								
Over Voltage Protection	None								
Short Circuit Protection	Yes								
Ripple & Noise (p-p)	2% Max								
O/P Connector (1.8M Jack Lead)	2.1 & 2.5mm Interchangeable								
SAFETY:									
Hi Pot Test I/P-O/P	4242VDC								
Insulation I/P-O/P	50Mohm								
TEMPERATURE:									
Operating	0 to 70°C Derates Linearly From 100 to 50% Load From 40 to 70°C								
Storage	-40 to 85°C								
HUMIDITY:									
Operating	5 to 95% Non Condensing								
Storage	Not Specified								
INPUT:									
Voltage	90 to 264VAC								
Frequency	47 TO 63Hz								
Current RMS (Max)	0.4A								
Inrush Current	15/30A								
Leakage Current	0.75mA Max								
Efficiency (Min)	60%								
MTBF	Not Specified								
Safety	UL 60950-1, CSA C22.2 No. 60950-1, EN 60950-1								
Additional Safety	PSE	PSE	PSE	PSE	PSE	PSE	PSE	PSE	PSE
EMI	EN 55022, EN 61000-3-2, EN 61000-3-3								
EMC	EN 55024, (IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11)								

Dimensions:

Weight: 165g Approx

