



24Vac Wall-Mounting PSU Range

Specifications:

Part		T3445SA	T3867SA	T3868SA
Input	Voltage	230VAC	230VAC	230VAC
	Frequency	50Hz	50Hz	50Hz
	Magnetising Current	70mA Max.	60mA Max.	60mA
	Mains Lead	1.8M with Bare Ends	1.8M with Bare Ends	1.8M with Bare Ends
	Mains Plug	Available on request	Available on request	Available on request
Output	Voltage	24Vac (+/- 10%)	24Vac (+/- 10%)	24Vac (+/- 10%)
	Voltage (no load)	28.6Vac (+/- 10%)	26.6Vac (+/- 10%)	26.9Vac (+/- 10%)
	Current	750mA	2A	3A
	Power	18VA	48VA	72VA
	Output Wire	1.8M with Bare Ends	1.8M with Bare Ends	1.8M with Bare Ends
	Output Plug	Available on request	Available on request	Available on request
Additional Information	Safety	CE	CE	CE
	Hi Pot Test I.P.-O.P.	3.75KVac (1 Min.)	3.75KVac (1 Min.)	3.75KVac (1 Min.)
	Insulation I.P.-O.P.	100Mohm	100Mohm	100Mohm
	Operating Temp.	0 - 40°C	0 - 40°C	0 - 40°C
	Temperature Rise	80°C Max.	80°C Max.	80°C Max.
	Weight	1.1kg (average)	1.1kg (average)	1.1kg (average)
	Dimensions (L x W x H)	106 x 55.5 x 48.5mm (inc. Mounting tabs)	97 x 72 x 68.5mm (inc. Mounting tabs)	97 x 72 x 68.5mm (inc. Mounting tabs)
IP Rating	N/A	N/A	Waterproof to IP66	

Schematic Diagram:

T3445SA



T3867SA



T3868SA



[Download individual Data Sheet](#)

[T3445SA
Click Here](#)

[T3867SA
Click Here](#)

[T3868SA
Click Here](#)

You might also be interested in...

Weatherproof & IP66 range of 12VDC & 24VAC PSU units. Available from stock or bespoke design tailored to your application. Click here for more details.



Stontronics Ltd

Chancerygate Business Centre, Cradock Road, Reading, Berkshire, RG2 0AH.

Tel: +44 (0) 118 931 1199 • Fax: +44 (0) 118 931 1145 • Email: info@stontronics.co.uk • Web: www.stontronics.co.uk



Please Note: Image shown is representative of entire range. Actual PSU image &/or drawings available in the individual data sheets.

Stontronics Ltd accepts no responsibility for typographical errors in the production of this leaflet. Product specifications are subject to change without notice.