



60W Wall-Mounting SMPSU Range

- Class II Switch Mode Power Supply with Wall-Mounting tabs
- 1 Year Warranty

Specifications:

Part		T4483ST	T4484ST
Input	Voltage Range	90~254VAC	90~254VAC
	Frequency Range	47~63Hz	47~63Hz
	In-Rush Current	30A (100VAC) 75A (240VAC)	30A (100VAC) 75A (240VAC)
	Input Current	1.5A Max. (90VAC)	1.5A Max. (90VAC)
	Standby Power	0.5W (no load)	0.5W (no load)
	Mains Lead	2M with bare ends.	2M with bare ends.
	Output	Voltage	12Vdc (+/-0.6V)
Min. Load current		0mA	0mA
Max. Current		5000mA	2400mA
Power		60 Watts	60 Watts
Line Regulation		+/- 1%	+/- 1%
Load Regulation		+/- 5%	+/- 5%
Ripple & Noise		150mVp-p (max.)	150mVp-p (max.)
Efficiency		75% (@ full load)	75% (@ full load)
Output Lead		1.5M	1.5M
Output Plug		2.1mm C+ve Plug	2.1mm C+ve Plug
Additional Information		Safety	UL60950, FCC part 15, CE EN60950 / EN55022
	Switching Frequency	65K Hz Typical	65K Hz Typical
	Hi Pot Test I.P.-O.P.	3000Vac 10mA/min.	3000Vac 10mA/min.
	Insulation I.P.-O.P.	500VDC 10Mohm min.	500VDC 10Mohm min.
	Operating Temp.	-20 - 40°C	-20 - 40°C
	Operating Hum.	20% - 90%	20% - 90%
	MTBF	50,000 hours (@25°C)	50,000 hours (@25°C)
	Dimensions (L x W x H)	138 x 51 x 32mm (inc. Mounting tabs)	138 x 51 x 32mm (inc. Mounting tabs)
Download individual Data Sheet		T4483ST Click Here	T4484ST Click Here

You might also be interested in...

Our range of 42Watt Wall Mounting Switch Mode Power Supplies fitted with a UK mains plug as standard. 12Vdc & 24Vdc models available. Click here to find out more.



Stontronics Ltd

Chancerygate Business Centre, Cradock Road, Reading, Berkshire, RG2 0AH.

Tel: +44 (0) 118 931 1199 • Fax: +44 (0) 118 931 1145 • Email: info@stontronics.co.uk • Web: www.stontronics.co.uk

Please Note: Image shown is representative of entire range. Actual PSU image &/or drawings available in the individual data sheets.

Stontronics Ltd accepts no responsibility for typographical errors in the production of this leaflet. Product specifications are subject to change without notice.